

The Visades Touch-Control II UV-Disinfection-Units are certified according to ÖVGW. Due to the wide range of functions for integration into digital networks using proven components, the UV systems offer maximum reliability for small and large waterworks.

GENERAL	
Manufacturer	VISADES
ÖVGW Certificate	W1.879
DVGW Certificate	DW-9182DN0667
SVGW Certificate	Upon Request
Model	
Number of lamps	12
Flow range	102,51 - 846,40 m³/h
Minimum UV transmission	5% T100mm / 74,11% T10mm
Chamber material	V4A / SS316L
Operating pressure (bar)	PN10
Connection	FL DN350 PN10
Control Unit	
Display	4,3" Touch-Display
Mains connection	400VAC/50Hz
Total power (W)	5450
Supply line protection (A)	25
Control cabinet protection (A)	6/13
Protection class	IP54
UV-Lamp	
Lamp type	ST400
Power (W)	410
UVC power (W)	410

UV-Unit Includes:	Functionality
<ul style="list-style-type: none"> -Stainless steel irradiation chamber V4A/SS316L -Immersion tube made of high-quality quartz glass - Powerful low-pressure UVC lamp - UVC sensor ÖNORM M5873-1 for monitoring irradiance - Electronic ballast with low energy consumption - Control unit in powder-coated steel housing IP54 - 4.3-inch color touchscreen, capacitive - Resolution 480x272, 65,000 colors - Connections for sampling taps - Connections for venting/draining 	<ul style="list-style-type: none"> - ÖNORM 5873-1 Functions - Various operating meters - System status messages - Pre-warning and shutdown point messages - Irradiance display in W/m² - Chamber temperature monitoring - Analog UV value output - Lamp status display - Programmable data logger - Trend recording - Alarm support - Controller battery backup input - Adjustable system overview

